

IVOLTAIR

ELECTROSTATIC AIR CLEANER

IV15200 & IV15200UV



Electrostatic Air Cleaner



KITCHEN EXHAUST APPLICATIONS

- Smoke
- Grease
- Wood-fire
- Odor
- Display mobile cooking stations
- Vent less hood



INDUSTRIAL APPLICATIONS

- Oil
- Fumes
- Dust
- Coolant
- CNC workshops



HVAC APPLICATIONS

- Lounges
- Smoking rooms
- Return air
- Supply air

IV15200 & IV15200UV

Technical specification

Dimensions (mm)	H1030*696*L1865
Metal of construction	MS CRCA 1.6MM
Finishing	7 tanks Processed, Grey powder coat
Electrical parameters	110 - 220V AC, 50HZ, 300 Watts Max
High voltage	Dual output PWM technology power supply unit short circuit, arc protection and auto reset 1.0 Second recovery time CE certified power supply unit
Safety features	Door safety switch integrated, earth leak trip
Air volume	15200 CFM - 20400 CMH
Particle capture range	0.1 Micron Meter - 10 Micron Meter
Maximum efficiency	95% DOP single pass test 97% DOP double pass test complies ANSI / ASHRAE 52.2-2017 standard test procedure
ESP cell technology	Dual stage (Ionizer & collector)
No of cells	6
Mesh filters	06 of aluminum mesh with SS304 frame
BMS connectivity	No volt Realy for BMS monitoring / alarm integration
Operator interface	Green LED - Healthy Red LED - Clean / Maintenance Power on/off switch AC protection fuse
Installation type	Ceiling suspended, floor and stand mount.

UV details (IV15200UV) for odor removal & air disinfection application

UV lamp wattage	130W * 06
UV output	660 micro watt/sq cm
OZONE output	12.6 Grams/hour (at standard conditions)
Rated life	10000 hours
Control unit	Digital timer with run hours Display
Operator interface	UV on blue LED indication

Complies **ASHRAE 50.2-2017** Standard for filter efficiency test

Complies **NFPA96** Safety standard for ventilation application

Complies **NFPA79** electrical standard

Complies **IS2418** standard for UV lamps

Complies **IS13021** standard for UV ballast

Complies **CE** standard for high voltage power supply

IVOLTAR® Electrostatic Air Cleaner comes with BDC™ enabled, Bi-directional configuration this enables user friendly installation regardless of directional limitation

Registered Design



Product of India

Maximum efficiency of the machine achieved within minimum specified air velocities and proper duct work design. IVOLTAIR® and BDC™ are the registered properties of its respected organizations

Company contact information

🏠 Envisync Systems Pvt Ltd
Hyderabad TS India.

✉️ sales@ivoltair.com

🌐 www.ivoltair.com

As a part of continues product development this document will be subjected to upgrade, change and modify without any notice, please check for updated document timely.